

WO2004113088

Publication Title:

DEVICE FOR DETECTING END OF PAPER IN A PRINTER

Abstract:

Abstract of WO2004113088

The device (18) for detecting end of paper comprises a support (43) mounted on a wall (26) of a printer (10) of receipts, obtained from a tape (12) of paper wound on a roll (14), contained in a housing (15) of the printer (10). The printer (10) is preferentially employed at a Point Of Sale (POS) and may be arranged on a horizontal work plane (21) set on its base (22), or inclined by about 90 DEG, on a front wall (24). As a result, the roll (14) is set into the housing (15) alternatively in two positions, corresponding to the inclination assumed by the printer. A detecting lever (54) in hinge-mounted on the support (43) and is provided with two arms (55, 56) spread apart, forming an angle of approximately 120 DEG. Fixed to each of the ends of the arms (55, 56) is a projecting element (58, 60), each of which suitable for engaging a hole in a central sprocket (17) of the roll (14), when the latter has reached its minimum dimension, in which a given length of tape remains of the sprocket (17), indicating that the latter is closed to running out. The two projecting elements (58, 60) are positioned in such a way that only one of these enters the hole in the sprocket (17), when the printer (10) is set in one of the two positions; the support (43) is moved linearly on the wall (26) by way of a toothed cam (47), in order to adapt the position of each of the projecting elements to the dimensions of the sprocket (17) of the paper roll.

Data supplied from the esp@cenet database - Worldwide

Courtesy of <http://v3.espacenet.com>

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 December 2004 (29.12.2004)


PCT

(10) International Publication Number
WO 2004/113088 A1

- (51) International Patent Classification⁷: **B41J 29/48**, 11/00
- (21) International Application Number: **PCT/IT2004/000360**
- (22) International Filing Date: **22 June 2004 (22.06.2004)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data: **IT02003A000475** 25 June 2003 (25.06.2003) **IT**
- (71) Applicant (for all designated States except US): **OLIVETTI TECNOST S.P.A.** [IT/TT]; Via Jervis, 77, I-10015 Ivrea (IT).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **COLOMBI, Alberto** [IT/TT]; c/o olivetti Tecnost S.P.A., Via Jervis, 77, I-10015 Ivrea (IT). **SALUSSOLIA, Plero** [IT/TT]; c/o Olivetti Tecnost S.P.A., Via Jervis, 77, I-10015 Ivrea (IT).
- (74) Agent: **GALLO, Marlo**; c/o Telecom Italia S.P.A., CLA-Ufficio Brevetti, Via Jervis, 11, I-10015 Ivrea (IT).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SI, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: **DEVICE FOR DETECTING END OF PAPER IN A PRINTER**



(57) Abstract: The device (18) for detecting end of paper comprises a support (43) mounted on a wall (26) of a printer (10) of receipts, obtained from a tape (12) of paper wound on a roll (14), contained in a housing (15) of the printer (10). The printer (10) is preferentially employed at a Point Of Sale (POS) and may be arranged on a horizontal work plane (21) set on its base (22), or inclined by about 90°, on a front wall (24). As a result, the roll (14) is set into the housing (15) alternatively in two positions, corresponding to the inclination assumed by the printer. A detecting lever (54) in hinge-mounted on the support (43) and is provided with two arms (55, 56) spread apart, forming an angle of approximately 120°. Fixed to each of the ends of the arms (55, 56) is a projecting element (58, 60), each of which is suitable for engaging a hole in a central sprocket (17) of the roll (14), when the latter has reached its minimum dimension, in which a given length of tape remains of the sprocket (17), indicating that the latter is closed to running out. The two projecting

elements (58, 60) are positioned in such a way that only one of these enters the hole in the sprocket (17), when the printer (10) is set in one of the two positions; the support (43) is moved linearly on the wall (26) by way of a toothed cam (47), in order to adapt the position of each of the projecting elements to the dimensions of the sprocket (17) of the paper roll.

**Declarations under Rule 4.17:**

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations* AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE,

BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

- *of inventorship (Rule 4.17(iv)) for US only*

Published:

- *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

DEVICE FOR DETECTING END OF PAPER IN A PRINTERField of the invention

This invention relates to an end of paper detecting device for a printer, and more particularly to a device for detecting a predetermined remaining length of paper tape, that is left deliberately on the roll to inform the operator of the imminent
5 end of the tape.

Brief description of the state of the art

Generally the device is used to advantage on a printer of a type known in the art, for instance a specialized printer for retail Points Of Sale (POS).

10 A printer of this type is preferably a conventional type, parallel, thermal printer, in which information is printed on a tape of treated paper, which unwinds from a roll placed in an appropriate housing inside the casing of the printer; normally the paper roll is arranged with its outer surface resting through gravity on inclined planes, which maintain the roll in a stable position, to guarantee proper
15 unwinding of the tape during printing.

A specialized point-of-sale printer, as indicated above, is normally set on a horizontal plane, but in certain situations can also be inclined, for instance, set against a vertical plane and rotated though about 90°, to reduce the amount of space occupied on the work plane.

20 In the latter case, the housing for the paper roll is provided with further inclined planes, suitable for supporting and holding the roll in the correct position while the tape is unwinding, in a way compatible with the

printer's changed disposition.

Accordingly, the device for detecting end of paper must also be able to adapt easily to both positions of the paper roll, in order to correctly detect the approaching end of the tape, both when the printer is set on a horizontal plane, and
5 when the printer is inclined.

In the US patents No. 5,820,068 and 5,884,861 a printer of the type mentioned above is described, feedable with a paper roll and provided with equipment for detecting and reporting the imminent end of paper.

The equipment for detecting end of paper is located externally to the casing
10 of the printer and comprises a support mounted rotatably with respect to the casing.

Mounted on the support is a lever having a first protrusion suitable for engaging the hole in sprocket of the paper roll, when the roll has decreased in size, and a second protrusion suitable for lying against the edge of the roll to maintain
15 the first protrusion separate from the sprocket, in order to guarantee that the first protrusion penetrates into the hole in the sprocket only when the paper roll has decreased to a predetermined size, corresponding to the imminent end of the paper tape.

At this point the second protrusion is no longer lying against the side of the
20 roll and thus allows the first protrusion to penetrate into the hole in the sprocket, which causes the lever to turn, and this in turn actuates a microswitch to report the end of paper condition.

The detecting equipment support may be rotated manually between different angular positions, corresponding to the positions assumed by the paper roll when the printer is set on a horizontal plane, or when it is inclined, or again when it is rotated against a vertical support.

- 5 This end of paper detecting equipment has the drawback of requiring the intervention of an operator to adjust the orientation of the support each time that the printer's support orientation is changed and in function of the initial dimensions of the paper roll, inserted in the printer.

Summary of the invention

- 10 The main object of the present invention therefore is to produce a device for detecting end of paper for a printer, which does not have the drawback encountered in the known types of similar equipment.

 Another object of this invention is to produce a device for detecting end of paper which automatically adapts itself to the orientation assumed by the printer,
15 without requiring any operator intervention.

 A further object of the invention is to produce a device for detecting end of paper that is simple to construct and highly reliable.

Brief description of the drawings

- Figure 1 is a lateral, perspective view, in partial section, of a printer using
20 the device for detecting end of paper, as described by the present invention;

 figure 2 is a lateral, perspective view of the printer of Fig. 1, without a casing;

 figure 3 is a perspective view from the top of the printer of Fig. 2;

figure 4 is a lateral, perspective view of the printer of Fig. 2 with a respective cutting unit in overturned position;

figure 5 is a lateral, perspective view of the device for detecting end of paper, used on the printer of Fig. 1;

5 figure 6 shows a detail of the device of Fig. 5;

figure 7 is a longitudinal section of the printer of Fig. 1, when set on its base;
and

figure 8 is a longitudinal section of the printer of Fig. 1, when it is set on a frontal wall.

10 Detailed description of a preferred embodiment

With reference to figures 1 - 8, in which the numeral 10 is used to indicate a printer of the type used in points of sale (POS), preferably thermal type, which prints information on a tape 12 of treated paper, which unwinds from a roll 14 (Figs. 7 and 8), in turn accommodated in a housing 15 on the inside of a casing 16 of the printer 10. The roll 14 is generally made of a sprocket 17 on which the paper tape 12 is wound.

For clarity's sake, in figure 1 part of the casing 16 has been removed in order to reveal a device 18 for detecting end of paper, according to this invention.

20 The printer 10 comprises a main, fixed frame 20, bounded by a bottom wall 22 (Fig. 2) and a front wall 24. On the inside of the frame 20 is the housing 15 for the paper roll 14. The housing 15 is bounded by two lateral and opposite walls 25 and 26 (Fig. 3), and by a bottom wall 28, suitable for supporting the roll 14.

The printer 10 is prearranged to work indifferently in operating positions having different orientations, and is in particular suitable for working in one or the other of two operating positions, respectively indicated P1 and P2 (Figs. 7, 8).

In greater detail, the printer 10 may be set on a work plane 21 horizontal
5 with the base 22 (Fig. 7) or, in certain situations, to reduce the space occupied on the work plane 21, it may also be set inclining, for example, against a vertical plane, or rotated by about 90°, set on its front wall 24 (Fig. 8).

So that the paper roll 14 may always be correctly disposed, when the printer 10 is positioned in one or the other of the two above-mentioned positions P1 and
10 P2, the bottom wall 28 is divided into various support surfaces, having different inclinations, to offer the paper roll a stable support in each case.

Therefore the bottom wall 28 is divided into two pairs of support surfaces 30, 31 and 32, 33 (Figs. 7, 8), flat and variously inclined. When the printer 10 is set with the bottom wall 22 on the work plane 21, the roll 14 lies against the surfaces
15 30 and 31 (Fig. 7), whereas when the printer 10 is set with the front wall 24 on the same work plane 21, the roll 14 lies against the surfaces 32 and 33 (Fig. 8).

The printer 10 also comprises a printing group 35 (Figs. 4, 7) of the thermal, parallel printing type, known in the sector art, suitable for printing information on the tape 12 coming from the roll 14, and a cutting unit 38, consisting of an
20 automatic cutter with movable blades, of a type also known in the art, suitable for cutting a stub of tape, or receipt, after the printing and feeding of the tape 12.

In detail, the printing group 35 comprises a printhead 36, in the form of

a board and typically made of silicon, which is fixed upon a support mounted on the fixed main frame 20 and which bears a row of heating elements 36a.

In use, the printhead 36 is urged resiliently against a contrast roller or platen 35a, mounted rotatingly on a movable structure 40 hinge-mounted on the frame 20
5 and better described later on, with the tape 12 in between and thus pressed between the thermal printhead 36 and the platen 35a. In addition, under these conditions, the platen 35a rotates to produce feeding of the tape 12 and its unwinding from the roll 14, whereas at the same time the heating elements 36a of the printhead 36 are selectively excited for the printing, through thermal effect, of
10 information on the tape 12 of thermal or treated paper.

In turn, the cutting unit 38 is openable type and comprises a first blade provided on the frame and a second blade provided on the movable structure 40 (Fig. 4), in such a way that the two blades can be detached, and the cutting unit 38 opened, when the structure 40 is moved away from the fixed frame 20 to permit
15 access to the internal housing 15.

In particular, the structure 40 can be rotated about pins 42, from a closed position "C" (Fig. 2), in which the structure 40 is overturned on the frame 20 at the end opposite the front wall 24, to an open position "A" (Fig. 4), in which the structure 40 is overturned in the direction of the front wall 24.

20 In particular, rotation of the structure 40 with respect to the frame 20 is commanded by means of the rotation of a cover 39, in turn fulcrum-mounted on the frame 20 by means of a pin 51 (Fig. 7).

The structure 40 is connected to the cover 39 by means of a link-block made of a pin 41, projecting laterally from the structure 40 and engaging with a groove 41a in the cover 39.

In addition, the cover 39 is kept in the closed position "C" by means of a latch, not depicted, which, when it is opened by means of a button 49, causes the thermal head 36 to move away from the platen 35a; in this way, the cover 39 and the structure 40 may be rotated with respect to the frame 20 without sliding occurring under the load of the heating elements 36a against the contrast roller 35a.

When the structure 40 is rotated into the position "A", the housing 15 stays open, and the operator can have access to it in order to replace the finished roll with a new roll 14, or for ordinary maintenance.

In particular, in position "A", a new roll 14 can be easily and comfortably inserted in the housing 15, arranging the relative strip of paper 12 so that it passes over the printhead 36, so that, when the structure 40 is again rotated into position "C", the strip of paper 12 is already correctly positioned for printing, between the printhead 36 and the platen 35a, and also for cutting by the cutting unit 38.

The device 18 for detecting end of paper is shown in figure 5, and comprises a support 43, which can slide linearly on the wall 26 of the housing 15, steered by a guide 44, engaging in a groove 45 of the wall 26 (Fig. 3). The position of the support 43 is controlled by a regulating member (Fig. 2), consisting of a rotating arm 46, screwed on to pins 42 and integral with a toothed cam 47; the toothed cam 47 engages a tooth (Figs. 1, 5) of the support 43, so that for a rotation of the arm

46, there is a corresponding linear movement of the support 43. A spring 50, placed between the support 43 and a projection 52 of the frame 20 resiliently contrasts the movements of the support 43, guaranteeing a regular movement in the two directions.

5 Hinge-mounted on the support 43 is a detecting lever 54 (Figs. 5, 6), provided with two arms 55 and 56, which diverge one from the other, and together form an angle of about 120°. Each of the arms 55 and 56 bears on its end a projecting element 58 and 60 respectively, said projecting elements 58 and 60 extending substantially in a direction perpendicular to the plane of the lever 54,
10 towards the inside of the housing 15, passing through two apertures 62 and 64 in the wall 26 (Fig. 3).

The two projecting elements 58 and 60 are constantly urged towards the inside of the housing 15 by means of an elastic member, not shown in the drawings, which is mounted on the support 43 and which acts on the lever 54, so
15 that each of the projecting elements rests against an edge of the paper roll 14, when it is inserted in the housing 15, in each of the two positions of the printer 10.

To facilitate the insertion of a new paper roll, when the structure 40 is rotated to the open position "A", the elements 58 and 60 are kept back from the wall 26 by means of a wedge element 57 integral with the structure 40 (Figs. 2, 4)
20 and provided for cooperating with the lever 54.

Accordingly when the structure 40 is rotated to the closed position "C", one or the other of the projecting elements 58 and 60 rests against an edge of the paper roll 14, until when the length of the paper tape remaining on the roll 14

reaches a predefined, minimum value, in correspondence with which, the projecting element concerned, 58 or 60, enters a hole 19 in the sprocket 17 of the roll 14, and causes rotation of the lever 54, which in turn activates a microswitch 68, mounted on the support 43, thus generating an end of paper signal.

5 For clarity's sake, the position of the paper roll 14 when it reaches its minimum dimension and therefore either one or the other of the projecting elements 58 and 60 penetrates into the sprocket 17, is indicated with the dot and dash line in Figs. 7 and 8.

According to one of the objects of this invention, the arms 55 and 56 of the lever 54 are sized in such a way that only one of the two projecting elements 58, or 10 60, can engage the hole 19 in the sprocket 17, when the paper tape is close to running out, in whatever way the printer 10 is oriented on the work plane 21.

In particular, when the printer 10 is set on the work plane 21 horizontal with the base 22 (Figs. 2, 7), the new roll 14 of paper is inserted freely in the housing 15, as the lever 54 is kept away from the structure 40 rotated into position "A" (Fig. 4). The new roll 14 is therefore disposed by gravity against the surfaces 30 and 31 of the bottom wall 28 (Fig. 7).

In this situation, the projecting element provided for reporting the end of paper condition, for instance the projecting element 58, remains against the edge 20 of the paper roll 14, while the latter decreases in diameter on account of the tape being withdrawn.

Then, when the dimension of the paper roll 14 reaches its minimum level, corresponding to the scheduled remaining length of the paper tape, still wound on

the sprocket 17, the projecting element 58 can penetrate into the hole 19 in the sprocket 17 of the roll, while the projecting element 60 remains free to move in the inside of the housing 15, since the roll is no longer capable of impeding its movement, on account of having reached the minimum dimension.

5 A similar situation arises when the printer 10 is set on the work plane 21 with its front wall 24 (Fig. 8).

 In this position a new roll 14 of paper lies against the surfaces 32 and 33 of the bottom wall 28 and, when the paper roll 14 has reached its minimum dimension, corresponding to the scheduled remaining length, the projecting
10 element 60 can penetrate into the hole 19 of the corresponding sprocket 17, while the projecting element 58, now on the outside of the clearance area of the roll 14, does not interfere with its edge.

 It remains understood, therefore, that changes in the shape and size of the various components, and also improvements, or additions and/or substitutions of
15 parts may be made to the device for detecting end of paper for a printer, according to this invention, without departing from the scope of the invention.



CLAIMS



1. Device for detecting end of paper for a printer (10), wherein said paper (12) is wound on a roll (14) placed in a housing (15), said roll (14) being suitable for assuming different positions in said housing (15), respectively when said printer is in a first (P1), or in a second (P2) operating position, said detecting device comprising sensor means (54, 58, 60) suitable for cooperating with a sprocket (17) of said roll (14), when said roll contains a predetermined minimum length of paper, **characterized in that** said sensor means comprise a lever (54) movable with respect to said housing, comprising two arms (55, 56) bearing at one end a respective projecting element (58, 60), each projecting element (58, 60) being suitable for engaging a hole (19) in said sprocket (17), respectively when said printer (10) is in said first (P1), or in said second (P2) operating position.
2. Device as in claim 1, **characterized in that** said lever (54) is fulcrum-mounted on a support (43) mounted on a wall (26) of said housing (15), said lever (54) assuming one or the other of two angular positions according to a plane perpendicular to said wall (26), respectively when said projecting elements (58, 60) are lying against the edge of said roll (14), or when only one of said projecting elements (58, or 60) engages the hole (19) in said sprocket 17.
3. Device as in claim 2, **characterized in that** said support (43) is linearly sliding on said wall (26) and is moved by a cam-type regulating member (46, 47), rotating on said wall (26), to adapt the position of each of said projecting elements (58, 60) to different dimensions of said sprocket (17).

4. Device as in any of the previous claims, **characterized in that** said lever (54) cooperates with a microswitch (68) to generate an end of paper signal when one or the other of said projecting elements (58, or 60) engages the hole (19) in said sprocket (17).
- 5 5. Device as in any of the previous claims, **characterized in that** said two arms (55, 56) of said lever (54) are reciprocally spread apart and together form an angle of about 120°.
6. Device as in any of the previous claims, **characterized in that** said two arms (55, 56) are sized in such a way that only one of said projecting elements (58, or 60) can engage said hole (19), respectively in each of said operating positions of said printer (10).
- 10 7. Device as in any of the previous claims, **characterized in that** said housing (15) is provided with at least two groups of support surfaces (30, 31 and 32, 33), the support surfaces of each of said groups being suitable for supporting said roll (14), respectively when said printer (10) is in said first, or in said second operating position.
- 15 8. Printer (10) for receipts made from a paper tape (12) wound on a roll (14) placed in a housing (15) of said printer (10), said roll (14) being suitable for assuming different positions in said housing (15), respectively when said printer is in a first (P1), or in a second (P2) operating position, said printer comprising a printing group for printing information on said receipts, a cutting unit for separating said receipts from said paper tape, and a device for detecting end of paper comprising sensor means (54, 58, 60) suitable for cooperating with a sprocket (17)
- 20

of said roll (14), when said roll contains a predetermined length of paper, said printer being **characterized in that** said sensor means (54, 58, 60) comprise a lever (54) that is movable with respect to said housing, provided with two arms (55, 56) bearing at one end a projecting element (58, 60), each projecting element (58, 60) being suitable for engaging a hole (19) in said sprocket (17), respectively when
5 said printer (10) is in said first (P1), or in said second (P2) operating position.

1/4








Fig. 5






Fig. 6



INTERNATIONAL SEARCH REPORT

International Application No
PCT/IT2004/000360

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B41J29/48 B41J11/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B41J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data, IBM-TDB

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 1 231 070 A (STAR MFG CO) 14 August 2002 (2002-08-14) the whole document	1,8
Y	PATENT ABSTRACTS OF JAPAN vol. 2000, no. 24, 11 May 2001 (2001-05-11) & JP 2001 206602 A (SEIKO INSTRUMENTS INC), 31 July 2001 (2001-07-31) abstract	1,8
A	PATENT ABSTRACTS OF JAPAN vol. 1998, no. 01, 30 January 1998 (1998-01-30) & JP 9 254474 A (SEIKO EPSON CORP), 30 September 1997 (1997-09-30) abstract	1-8

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the International filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the International filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

G document member of the same patent family

Date of the actual completion of the international search

30 September 2004

Date of mailing of the international search report

08/10/2004

Name and mailing address of the ISA

Europeaan Patent Office, P.B. 6818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Van den Meerschaut, G

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IT2004/000360

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 1231070	A	14-08-2002	JP 2002234223 A	20-08-2002
			EP 1231070 A2	14-08-2002
			US 2002109037 A1	15-08-2002
JP 2001206602	A	31-07-2001	NONE	
JP 9254474	A	30-09-1997	JP 3491435 B2	26-01-2004